

Technical Data Sheet

2000-1619-R Calibration Kit

Type 7/16(f)
DC to 6 GHz, 50 Ω



This calibration kit has been designed to provide superior measurement results when used with precision instruments. It is designed for use in field environments. It is a high precision component and should be handled with proper care. Excessive shock, torque, or power should be avoided to prevent permanent damage.

Specifications are guaranteed under the following conditions:

1. Unit is operated within specified temperature range.
2. Unit has not been subjected to damage from mishandling.

Length, capacitance, and inductance are nominal values.

Open and Short Phase and DC Resistance specifications are typical.

Operating Temperature Range	0 °C to +50 °C
Storage Temperature Range	-55 °C to +90 °C

For the latest information, sales, or service, visit: www.anritsu.com

2000-1619-R Calibration Kit TDS
Copyright December 2021 Anritsu Company, USA
All Rights Reserved

© Anritsu All trademarks are registered trademarks of their respective companies. Data subject to change without notice. Anritsu prints on recycled paper with vegetable soybean oil ink.



11410-01098



C

2000-1619-R Calibration Kit Specifications

Open	Spec
Length	26.2 mm
C0 (1E-15) F	185
C1 (1E-27) F/Hz	23
C2 (1E-36) F/Hz ²	-184
C3 (1E-45) F/Hz ³	104

Short	Spec
Length	29.0 mm
L0 (1E-12) H	0.0
L1 (1E-24) H/Hz	0.0
L2 (1E-33) H/Hz ²	0.0
L3 (1E-42) H/Hz ³	0.0

Load	Spec
DC Resistance	50 Ω \pm 0.5 Ω
Return Loss (DC to 4 GHz)	\geq 35 dB
Return Loss (4 GHz to 6 GHz)	\geq 32 dB
Max Power	1.0 W