


MT9083 Series

MT9083A2/B2/C2 ACCESS Master™

850/1300 nm OTDR for Multimode Fiber

1310/1490/1550/1625/1650 nm OTDR for Single Mode Fiber





All-in-one Solution that Reduces Testing Times to Install and Maintain FTTx, CATV, LAN, Access and Metro Networks

850/1300 nm OTDR for MMF
1310/1490/1550/1625/1650 nm OTDR for SMF

MT9083 SERIES ACCESS MASTER OVERVIEW

Optical fibers are a key technology in today's modern communications systems, including access networks such as FTTx, CATV, and optical LANs. Moreover, optical-fiber technologies are playing increasingly important roles in mobile communications and digital broadcasting systems. Technicians maintaining these diverse systems are forced to carry a large variety of test equipment on-site, including OTDRs, Light Sources, Optical Power Meters, Visible Light Sources, etc. On the other hand, fiber construction requires measuring instruments with different functions and performance. As an example, FTTx access networks use single mode (SM) fiber whereas optical LANs use multimode (MM) fiber. In addition, core and backbone networks utilize long fibers while optical access networks use short fibers, both requiring different types of measuring instruments with different performance. But now Anritsu's new line of MT9083 ACCESS Master OTDRs solves all these problems by providing all the measurement functions and performance required for optical fiber construction and maintenance in a compact, lightweight, all-in-one unit that eliminates the burden of carrying many different test sets and instruments on-site. Whatever your work, construction or maintenance, long haul or intra-building, Anritsu has an MT9083 model for your needs.

ACCESS Master Key Features

- Specialized testing modes simplify operation
- High resolution and high dynamic range ensure quick and thorough fiber evaluation
- Intelligent analysis software identifies problem splices, connectors and even macrobends
- Rugged, sealed design provides years of service in the most challenging environments
- Large 7-inch enhanced display for easy viewing of results indoors or outdoors
- Test multiple wavelengths with a single unit - single mode, multimode or both
- Unique in-service testing without the need for external filters
- New feature offering easy graphical summary & PDF reporting
- Verify connector quality with optional connector inspection microscope
- Password protection feature for important file on-internal memory
- Bluetooth, Wi-Fi and Ethernet connectivity*

*: These features use an USB Ethernet converter, USB Wi-Fi dongle, or USB Bluetooth dongle.

The *Bluetooth*® wordmark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Anritsu is under license.

Full SCPI Command Support for Remote Operation or Automated Testing Multiple Models to Meet Any Testing Requirement


- MT9083A2: General purpose, enhanced range with full 1 × 64 PON support, up to 39 dB.
- MT9083B2: High performance, enhanced range with full 1 × 64 PON support, up to 42 dB.
- MT9083C2: Ultra-high performance, enhanced range with full 1 × 128 PON support, up to 46 dB.

MT9083 Series

MT9083A2/B2/C2 ACCESS Master™

850/1300 nm OTDR for Multimode Fiber
1310/1490/1550/1625/1650 nm OTDR for Single Mode Fiber





New Feature Highlight



Enhanced Model

Anritsu is now pleased to announce the enhanced MT9083A2/B2/C2 models. The ACCESS Master MT9083x2 now features a 7-inch widescreen TFT-LCD display for use both indoors and outdoors, enhanced battery operation time (up to 12 hours), increased operating temperature range (-10° to +50°C) and new short-cut function keys.

Enhancements:

- Larger (7 inch), higher resolution (800 × 480) display with LED backlight
- Longer battery operation time: Up to 12 hours
- Wider operating temperature range: -10° to +50°C
- New shortcut keys to simplify operation: quickly change between trace and event table or access set-ups and mass storage
- Lighter – now only 2.6 kg (5.7 lbs)!

Optimized for Verifying PON Splitters Up to 1 × 128 Count

Many OTDRs claim to be able to test splitter-based, passive optical networks (PON) but the MT9083 delivers in a way others wish they could. With its high dynamic range and quick data acquisition, the MT9083 provides unparalleled resolution of single or closely spaced, cascaded splitters up to an industry-leading 1 × 128 count.







Fig 1: Typical PON 1 × 64 count System Measurement from the customer premise.

The MT9083 Series Enhanced Range Mode and a Pulse width of 100 ns provides excellent dynamic range while not compromising deadzone resolution to clearly display multiple, high loss splitters.



Designed with the Features that Matter Most

When buying products, you tend to choose ones that are innovative and from established companies. When you need to install and maintain optical networks, this should also apply. With over 50 years of combined OTDR design, Anritsu, delivers the features that matter.

Having been in the test and measurement business for a long time, we understand that things like performance, portability, reliability, easy operation and of course price are important.

Long Battery Life

Since AC power is not always available where you need it, especially at fiber pedestals, the MT9083 typically provides up to 12 hours of operation on a single charge. This coupled with an optional car cord (for cigarette lighter operation) guarantees the MT9083 is ready when you are.

Portable

With its light weight design and user friendly dimensions, the MT9083 is perfect for the outside plant environment and can easily be managed with one hand. The shoulder strap (part of the protector option) further increases portability when travelling from the truck to the testing site.

Rugged

The MT9083 features a solid casework with no fans or vents to keep dust or moisture from entering the unit. In addition, the protector option (MT9083A2/B2/C2-010) includes rubber bumpers and a display cover for additional protection from those minor mishaps.

Generous Data Storage

With the ability to store up to 1,000 traces in internal memory and up to 30,000 via a USB device, the MT9083 offers plenty of storage for collecting and managing data.

No Experience Required

With the ACCESS Master, the experience is built in. With specialized testing modes, automatic parameter selection, PASS/FAIL indicators as well as features to virtually eliminate the chance to get "bad" results, the MT9083 can make anyone seem like a 20 year veteran. Let it help you master your network.

Easy "drag and drop" File Transfers

When the MT9083 is connected to a PC via a USB cable, the internal memory of the ACCESS Master can be directly accessed. Data can be selected, dragged and dropped into the PC memory, greatly simplifying file transfers. The MT9083 also supports use of USB memory sticks.

Common OTDR Data Format

The MT9083 supports the universal Telcordia SR-4731 (issue 2) format making it compatible with not only legacy Anritsu and NetTest products, but with many other vendors data.

Free and Simple Software Upgrades

Firmware upgrades are easily performed via USB and available from the Anritsu website for registered users or through Anritsu customer support.

Active Fiber Check

Not only can OTDR measurements be affected when the optical fiber is in-service but there is a potential risk of damage to the transmitter and OTDR receiver. To prevent these problems, the MT9083 verifies if light is present before starting measurement and will not transmit if it is.

An on-screen warning and internal OTDR protection are also part of this useful feature.


Integrated Macrobend Detection

With many technicians making the switch from copper installations to optical fiber, installation issues such as macrobends are bound to occur. To help prevent this, Anritsu has developed a macrobend detection feature for the MT9083 that will alert technicians when a possible macrobend is present. This provides a higher quality of service for the customer and eliminates costly troubleshooting for you.

Multiple Wavelengths and Models

Whether you need singlemode and multimode testing capabilities in one unit or standard 1310 nm & 1550 nm installation wavelengths plus 1650 nm with a filter for maintenance testing. The ACCESS Master can be configured to meet your individual needs.





Compact, Light Weight and All-in-one


With its versatile built-in functions, the ACCESS Master offers the ideal solution for efficient optical fiber construction and maintenance.

All-in-one Test Set

The MT9083 delivers full featured OTDR performance plus loss test set and quality of service measurement in a surprisingly small and lightweight package. At only 28.4 cm wide x 20 cm tall x 7.7 cm deep and 2.6 kg (5.7 lbs.), it is field portable, yet rugged enough to withstand the outside plant environment. When equipped with power meter and visual light source options, it replaces several, larger pieces of test equipment.



- 1 Up to 10 hours battery life plus quick recharge
- 2 Optical Power meter options with up to +30 dBm measurement range
- 3 Visible laser source for easy fiber identification and bend/break location
- 4 Up to three wavelengths from a single port for any application
- 5 Dual USB ports for easy data transfer and connector inspection microscope
- 6 Dedicated short-cut keys to quickly move between events or view trace fill screen
- 7 Numeric keypad with dedicated keys for easy operation
- 8 Dedicated function keys for selecting parameters
- 9 Rotary dial for precision cursor movement
- 10 Arrow keys for quick zooming and navigation through menus
- 11 START key for simple one-button testing
- 12 7 inch indoor/outdoor color TFT-LCD display with LED backlight



Exceptional OTDR Performance from the World's First OTDR Manufacturer

Evaluation of access networks ranging from a few kilometers to metro networks reaching up to 100 km in length is becoming commonplace, requiring OTDRs to have the performance and functions for evaluating both short and long fibers. Designed with this in mind, the ACCESS Master delivers on both fronts.

Improved Short Fiber Analysis

An event dead zone of less than 1 m (80 cm typical) and a sampling resolution of 5 centimeters allow the MT9083 to evaluate connections and troubleshoot central office, FTTx and intra-building faults with ease – providing a level of detail never before seen.




Fig. 3: With its high resolution optics, the MT9083 provides exceptional detail allowing users to quickly determine where the problem is—even when events are closely spaced.

Extended Range Testing of 200 + km Fibers

In addition to its superb high-resolution performance, the MT9083 also features up to 46 dB of dynamic range allowing it to easily test 200 + km spans making it a very useful tool for any network type.




Fig. 4: Spans of over 200 km are also easily tested making the MT9083 the only tool you will need - for any network type.

Convenient Features

Full PON Testing

Many OTDRs claim to be able to test PONs but being able to do it with both high resolution and high range is what sets the MT9083 series apart. Splitters up to a single 1 x 128 or closely spaced, cascaded splitters are completely and accurately measured with industry leading resolution.




Fig. 5: The MT9083 series provides high range and excellent resolution of PON systems

Waveform Comparison Function

Compare current and stored trace data to easily assess changes over time and to locate problems before they affect service or compare traces at different wavelengths to identify installation issues such as macrobending.

Standard High Resolution Display

The MT9083 series now features a standard 7" high resolution display with excellent readability both indoors and outdoors – even in direct sunlight.

Dual-mode High Resolution/Enhanced Range Operation


While many OTDRs provide good deadzone resolution or high dynamic range, the MT9083 series features a dual-mode design that allows a single unit to excel in both categories. The user can simply select HIGH RESOLUTION (HR) mode or ENHANCED RANGE (ER) based on the current task at hand. When HR mode is selected, this mode provides good measurement range with an industry leading deadzone (<1 m). When ER mode is selected, it provides unparalleled performance for measurement distance, measurement speed and deadzone - allowing a 100 km fiber to be tested in less than 10 seconds. ER mode is also used for testing PON networks with up to 128 branches.

Up to 150,001 Data Points for Increased Accuracy

The MT9083 series also collects up to 150,001 with a resolution of just 2 m. This provides the necessary detail when installing and maintaining fiber spans.

Event Table with User Defined Thresholds

PASS/FAIL thresholds for key acceptance criteria such as splice loss, connector loss and reflectance can be set in the MT9083 allowing technicians to easily assess a fiber's condition. Failing values are clearly highlighted in the event table alerting technicians of potential problems.



A True All-in-One Tester

An OTDR, Optical Power Meter, and Visible Light Source are built into Anritsu's compact, light-weight MT9083 supporting tasks ranging from searching for faults in optical fibers to QoS evaluation to FTTx troubleshooting with just one unit.

Complete Loss Test Set Features

Standard Stabilized Light Source

The OTDR port also functions as a stabilized light source providing continuous wave, 270 Hz, 1 kHz and 2 kHz modulations for easy fiber identification. This is standard equipment on all single mode models - a chargeable option on most other OTDRs.

Standard or Optional Integrated Power Meter

In the base unit, the OTDR port also functions as an integrated power meter for verification of optical power levels. Additional power meter options are available for higher power transmissions and loop-back testing.

Visual Laser Source for Easy Fault Location and Fiber Identification

A Visible Light Source is useful for tracking down bad connections, splices and fiber management issues such as macrobends. The optional Visible Light Source is factory installed in the MT9083 and features up to 5 km (3 miles) of operation.

Others

Bluetooth, Wi-Fi and Ethernet Connectivity

The Bluetooth feature enables you to share files between the MT9083x2 series and a PC. The Wi-Fi and Ethernet features enable you to share files as well as use the remote GUI feature. You can connect the MT9083x2 and PC, and control the MT9083x2 series from a browser.



Bluetooth:
- Share file folder

Wi-Fi and Ethernet:
- Share file folder
- Remote GUI

Password Protection Feature

A password protection feature has been added to the MT9083. When you use this feature, users will be required to enter a password as soon as the system boots. Users will not be able to use the system until the password is authenticated. This feature is useful if you want to limit the use of your measuring instruments to designated users, or you want to protect important files on the system's on-internal memory.




Fig. 10: Password Setting

Video Inspection Probe (VIP) Application – Complete Connector Inspection

Data Table for Saved Results

Loss test set measurements for multiple wavelengths can be saved into a results table for easy comparison and archiving. The table can also be saved as a text file and exported to a PC spread-sheet program for further manipulation or integration into a standard company template.

Video Inspection Probe Support

When equipped with the optional connector video inspection probe (VIP), the MT9083 becomes a powerful tool for evaluating connector cleanliness and quality. Connector end faces can be safely viewed and images stored to document all aspects of your network. We have added a Pass/Fail analysis function to the conventional VIP. This new function inspects the state of the connector end using video. It can automatically inspect the end of the optical connector for defects and scratches (The automatic pass/fail determination is made in accordance with the IEC61300-3-35 standard.) You can also create a PDF report on the MT9083 series.




Fig. 11: VIP Mode





Fig. 12: PDF Report



Specifications

● MT9083A2/B2/C2 ACCESS Master Common Specifications

Dimensions and Mass	Without Protector (Option 010)	Dimensions: 270 (W) × 165 (H) × 61 (D) mm, 10.6 × 6.5 × 2.4 inches Mass: 1.6 kg, 1.9 kg including battery
	With Protector (Option 010)	Dimensions: 284 (W) × 200 (H) × 77 (D) mm, 11.2 × 7.9 × 3 inches Mass: 2.6 kg including battery
Display	7-inch TFT-LCD (800 × 480, with LED backlight), Indoor/Outdoor type	
Interface	USB 1.1, Type A × 1 (memory), Type B × 1 (USB mass storage)	
Data Storage	Internal memory: 1 GB (50,000 traces), External memory (USB): up to 32 GB	
Power Supply	12 V(dc), 100 V(ac) to 240 V(ac), Allowable input voltage range: 90 V to 264 V, 50 Hz/60 Hz	
Battery	Type: Lithium-ion Operating Time*1: 12 hours, Telcordia GR-196-CORE Issue 2, September 2010 Recharge Time: <5 hours (power off)	
Power Saving Functions	Backlight off: Disable/1 to 99 minutes Auto shutdown: Disable/1 to 99 minutes	
Vertical Scale	0.13, 0.33, 0.65, 1.3, 3.25, 6.5, 13 dB/div	
IOR Setting	1.300000 to 1.699999 (0.000001 steps)	
Units	km, m, kft, ft, mi	
Languages	User selectable (English, Simplified Chinese, Traditional Chinese, French, German, Italian, Korean, Portuguese, Russian, Spanish and Swedish - contact Anritsu for availability of others)	
Sampling Points*2	Normal: 5001, High density: 20001 or 25001, Very high density: 100,001 or 150,001	
Sampling Resolution	5 cm (min.)	
Reflectance Accuracy	Single mode: ±2 dB, multimode: ±4 dB	
Distance Accuracy	±1 m ±3 × measurement distance × 10 ⁻⁵ ± marker resolution (excluding IOR uncertainty)	
Distance Range	Single mode: 0.5, 1, 2.5, 5, 10, 25, 50, 100, 200, 300 km Multimode: 0.5, 1, 2.5, 5, 10, 25, 50, 100 km	
Testing Modes	Fiber Visualizer: Provides end/break location, end to end loss, fiber length, easy graphical summary, PDF report, PDF viewer Standard OTDR: User selectable automatic or manual set-up Construction OTDR: Automated, multi-wavelength testing Light source: Stabilized Light source (CW, 270 Hz, 1 kHz, 2 kHz output) Loss test set (optional): Power meter and Light source Connector Video Inspection Probe Visual fault locator (optional): Visible red light for fiber identification and troubleshooting	
Fiber Event Analysis	Auto or manual operation, displayed in table format User defined PASS/FAIL thresholds: - Reflective and non-reflective events: 0.01 to 9.99 dB (0.01 dB steps) - Reflectance: -70.0 to -20.0 dB (0.1 dB steps) - Fiber end/break: 1 to 99 dB (1 dB steps) Number of detected events: up to 99 Macrobend detection	
OTDR Trace Format	Telcordia universal. SOR, issue 2 (SR-4731)	
Other Functions	Real time sweep*3: 0.15 sec. Loss modes: 2-point loss, dB/km, 2-point LSA, splice loss, ORL Averaging modes: Timed (1 to 3600 sec.) Live Fiber detect : Verifies presence of communication light in optical fiber Connection check: Automatic check of OTDR to FUT connection quality Trace overlay and comparison, Template function, USB keyboard support, Remote control, Video output to PC Password protection feature Bluetooth, Wi-Fi and Ethernet Connectivity	
Environmental Conditions	Operating temperature and humidity: -10° to +50°C, <80% (non-condensing) Storage temperature and humidity: -20° to +60°C, <80% (non-condensing) Vibration: Conforming to MIL-T-28800E Class 3 Dust proof: MIL-T-28800E (Dust Exposure) Class 2 Drip proof: IP51 (IEC 60529), JIS C 0920 TYPE I	
CE	EMC	EN61326-1, EN61000-3-2
	LVD	EN61010-1
	RoHS	EN50581

*1: Typical, backlight off, sweeping halted at 25°C, 6 hours typical continuous testing


*2: Either high density value is selected depending on distance range

*3: Resolution: Low Density


● OTDR Specifications

MT9083C2							
Options	HR/ER Mode*4	Wavelength*5	Fiber Type	Pulse Width	Dynamic Range*6,*7	Deadzone (Fresnel)*8 (IOR = 1.500000)	Deadzone (Backscatter)*9 (IOR = 1.500000)
MT9083C2-053	✓	1310/1550 nm ±25 nm	Single Mode (SMF) 10/125 μm ITU-T G.652	3, 10, 20, 50, 100, 200, 500, 1000, 2000, 4000, 10000, 20000 ns	46/46 dB*11	≤1 m, ≤80 cm (typ.)	≤3.8/4.3 m
MT9083C2-057	✓	1310/1550/1625 nm ±25 nm			25/25 dB*10 (Pulse width: 100 ns)		
MT9083B2							
Options	HR/ER Mode*4	Wavelength*5	Fiber Type	Pulse Width	Dynamic Range*6,*7,*13	Deadzone (Fresnel)*8 (IOR = 1.500000)	Deadzone (Backscatter)*9
MT9083B2-053	✓	1310/1550 nm ±25 nm	Single Mode (SMF) 10/125 μm ITU-T G.652	3, 10, 20, 50, 100, 200, 500, 1000, 2000, 4000, 10000, 20000 ns	42/41 dB*11	≤1 m ≤80 cm (typ.)	≤5/5.5 m
MT9083B2-055	✓	1310/1550 nm ±25 nm, 1650 nm ±5 nm			42/41/35 dB*11		≤5/5.5/6.5 m
MT9083B2-056	✓	1310/1490/1550 nm ±25 nm			42/41/41 dB*11		≤6/6.5/6.5 m
MT9083B2-057	✓	1310/1550/1625 nm ±25 nm			40/39/38 dB*11		≤6/6.5/7.5 m
MT9083B2-058	✓	1310/1490/1550/1625 nm ±25 nm			42/41/41/40 dB*11		≤7/7.5/7.5/8.5 m
MT9083B2-063	✓	1310/1550 nm ±25 nm, 850/1300 nm ±30 nm	HYBRID (SMF/MMF)*12	SMF: above MMF: 3, 10, 20, 50, 100, 200, 500, 1000, 2000, 4000 ns 850 nm: Not support 1000, 2000, 4000 ns	42/41 dB*11 29/28 dB*11	≤5/5.5 m, ≤4/5 m (3/4 m typ.)	
MT9083A2							
Options	HR/ER Mode*4	Wavelength*5	Fiber Type	Pulse Width	Dynamic Range*6,*7,*13	Deadzone (Fresnel)*8 (IOR = 1.500000)	Deadzone (Backscatter)*9
MT9083A2-073	✓	1310/1550 nm ±25 nm	Single Mode (SMF) 10/125 μm ITU-T G.652	3, 10, 20, 50, 100, 200, 500, 1000, 2000, 4000, 10000, 20000 ns	39/37.5 dB*11	≤1 m ≤80 cm (typ.)	≤5/5.5 m
MT9083A2-055	✓	1310/1550 nm ±25 nm, 1645 nm to 1655 nm			38.5/37/34.5 dB*11		≤5/5.5/6.5 m
MT9083A2-057	✓	1310/1550/1625 nm ±25 nm			37/35.5/32.5 dB*11		≤6/6.5/7.5 m
MT9083A2-063	✓	1310/1550 nm ±25 nm, 850/1300 nm ±30 nm	HYBRID (SMF/MMF)*12	SMF: above MMF: 3, 10, 20, 50, 100, 200, 500, 1000, 2000, 4000 ns 850 nm: Not support 1000, 2000, 4000 ns	39/37.5 dB*11 29/28 dB*11	≤5/5.5 m, ≤4/5 m (3/4 m typ.)	
Laser Safety*14		IEC 60825-1: 2007 CLASS 1M: option 053, 055, 056, 057, 058, 063, 073 21 CFR1040.10 Excludes deviations caused by conformance to Laser Notice No. 50 dated June 24, 2007					

- *4: HR: High Resolution mode for Short dead zone.
ER: Enhanced Range mode for PON measurement.
- *5: 25°C, Pulse width: 1 μs (all except 850 nm, 1300 nm), 850 nm/1300 nm: 100 ns
- *6: Pulse widths: 20 μs (Options 053, 055, 056, 057, 058, 063, 073, 1310 nm/1550 nm) at Distance range: 100 km
Pulse width: 4 μs (Options 063, 1300 nm) at Distance range: 25 km
Pulse width: 500 ns (Options 063, 850 nm) at Distance range: 25 km
Averaging: 180 sec., SNR = 1, 25°C
- *7: Dynamic range (one-way back-scattered light), SNR = 1: The level difference between the RMS noise level and the level where near end back-scattering occurs.




- *10: Pulse width: 100 ns (ER Mode), Distance range: 100 km
Averaging: 180 sec., SNR = 1, 25°C
- *11: Typical. Subtract 1 dB for guarantee
- *12: At measurement of 50 μm/125 μm MM Fiber, the dynamic range drops by about 3.0 dB
- *13: At 1.65 μm: With background light, 1.31 μm/1.55 μm, -19 dBm CW light
- *14: Safety measures for laser products
This product complies with optical safety standards in IEC 60825-1, 21CFR1040.10 and 1040.11; the following descriptive labels are affixed to the product.



THIS PRODUCT COMPLIES WITH 21 CFR 1040.10 AND 1040.11 EXCEPT FOR DEVIATIONS PURSUANT TO LASER NOTICE NO. 50, DATED JUNE 24, 2007

- *8: Pulse width: 3 ns (Options 053, 055, 056, 057, 058, 063, 073)
Return loss: 40 dB, 25°C (Refer to the figure below)
- *9: Pulse width 10 ns, return loss 55 dB, Deviation ±0.5 dB, 25°C (Options 053, 055, 056, 057, 058, 063, 073. All except 850 nm/1300 nm)
Pulse width 3 ns, return loss 40 dB, Deviation ±0.5 dB, 25°C (Options 063, 850 nm/1300 nm)



Light Source Specifications – Standard on all models*15	
Stabilized Light Source (through OTDR port)	
Wavelength*17	Same as OTDR
Spectral Width*17	≤5 nm (1310 nm) ≤10 nm (850/1300/1490/1550/1625 nm) ≤3 nm (1650 nm)
Wavelength Accuracy	850/1300/1310/1490/1550/1625 nm: ±30 nm 1650 nm: ±5 nm
Fiber Type	Same as OTDR
Optical Connector	Same as OTDR
Output Power*17	-5 ±1.5 dBm
Output Stability*18	±0.1 dB
Modes of Operation*19	CW, 270 Hz, 1 kHz, 2 kHz
Laser Safety	Same as OTDR

Power Meter Specifications – Standard on all models*15	
Standard Integrated Power Meter*16 (through OTDR port)	
Maximum Input	+10 dBm
Measurement Range	-50 to -5 dBm
Fiber Type	Same as OTDR
Optical Connector	Same as OTDR
Accuracy*20	±6.5%
Setting Wavelengths	1310, 1550, 1625, 1650 nm (Options 053, 055, 057, 063, 073) 1310, 1490, 1550, 1625 nm (Options 056, 058)
Features	Store reference, loss table

Loss Test Set Specifications – Optional on all Models*17, *18			
Power meters (004, 005 and 007)			
Option Number	MT9083A2/B2/C2-007	MT9083A2/B2/C2-004	MT9083A2/B2/C2-005
Fiber Type	Single Mode: 10 µm/125 µm (G.652), Multimode: 62.5 µm/125 µm	Single Mode: 10 µm/125 µm (G.652) *PC only for UPC connector	Single Mode: 10 µm/125 µm (G.652)
Measurement Range*21	-67 to +6 dBm*22	-50 to +23 dBm	-43 to +30 dBm
Wavelength Range	750 nm to 1700 nm	1200 nm to 1700 nm	
Setting Wavelengths	850, 1300, 1310, 1383, 1490, 1550, 1625, 1650 nm	1310, 1383, 1490, 1550, 1625, 1650 nm	
Optical Connector	Universal – uses LP-XX adapters	Universal – uses JXXXX adapters (same as OTDR)	Universal – uses MA9005B adapters
Accuracy*23	±5%		
Modulation	CW, 270 Hz, 1 kHz, 2 kHz		
Features	Store reference, loss table		
Environmental	Operating temperature and humidity: 0° to +50°C, <80% (non-condensing)		

Visible Light Source (Option 002)	
Central Wavelength	650 nm ±15 nm (at 25°C)
Optical Output	0 ±3 dBm (CW)
Output Optical Fiber	10 µm/125 µm, SMF (ITU-T G.652)
Optical Connector	2.5 mm universal
Laser Safety*24	IEC 60825-1: 2007 CLASS 3R 21CFR1040.10 and 1040.11 Excludes deviations caused by conformance to Laser Notice No. 50 dated June 24, 2007
Environmental	Operating temperature and humidity: 0° to +50°C, <80% (non-condensing)

*15: Some models do not support power meter (See next page)

*16: If option 004, 005 or 007 is ordered, the standard integrated power meter is not available

*17: CW, 25°C

*18: CW, -10° to +50°C (±1°C) difference between max/min. values over 1 minute, SM fiber 2 m

*19: Modulation +1.5% with 10 minute warm up

*20: CW input, -20 dBm at 1550 nm, 23°C ±2 Using Master FC connector

*21: Peak power, subtract 3 dB for modulated tones

*22: -60 to +3 dBm (Option 007 @850 nm)

*23: CW, model 007: At -10 dBm, 1310 nm/1550 nm, At -10 dBm, 850 nm, 25°C

model 004/005: At 0 dBm, 1310 nm and 1550 nm, Using Master FC connector, After zero offset

*24: Safety measures for laser products

This option complies with optical safety standards in IEC 60825-1, 21CFR1040.10 and 1040.11; the following descriptive labels are affixed to the product.



THIS PRODUCT COMPLIES WITH 21 CFR 1040.10 AND 1040.11 EXCEPT FOR DEVIATIONS PURSUANT TO LASER NOTICE NO. 50, DATED JUNE 24, 2007

Standard Light Source and Power Meter Built-in

**LS: MT9083A2/B2/C2 standard built-in stabilized Light Source,
OPM: MT9083A2/B2/C2 standard built-in Optical Power Meter**


Options	Optical Port	LS	OPM
MT9083B2/C2-053	1310/1550 nm SM	✓	✓
MT9083A2-073	1310/1550 nm SM	✓	✓
MT9083A2/B2-055	1310/1550 nm SM	✓	✓
	1650 nm SM	✓	✓
MT9083B2-056	1310/1490/1550 nm SM	✓	✓
MT9083A2/B2/C2-057	1310/1550/1625 nm SM	✓	✓
MT9083B2-058	1310/1490/1550/1625 nm SM	✓	✓
MT9083A2/B2-063	850/1300 nm MM	✓	—
	1310/1550 nm SM	✓	✓

Battery Pack: Z0921A

Battery	Lithium Ion secondary battery
Voltage, Capacity	11.1 V, 4200 mAh
Dimensions and Mass	53 (W) × 19 (H) × 215 (D) mm, 330 g (typ.)
Environmental Conditions	Charging: +5° to +30°C, ≤80%RH
	Discharging: -20° to +60°C, ≤80%RH
	Storage: -20° to +50°C, ≤80%RH

AC Adapter: Z1625A

Rated AC Input	100 V(ac) to 240 V(ac), 50 Hz/60 Hz
Rated DC Output	12 V(dc), 5 A
Environmental Conditions	Operating: 0° to +45°C, 20 to 80% R.H.
	Storage: -20° to +70°C, 10 to 90% R.H.



Ordering Information

Please specify the model/order number, name and quantity when ordering.
The names listed in the chart below are Order Names. The actual name of the item may differ from the Order Name.

1) Specify Base Unit

Includes ACCESS Master OTDR, AC charger/adaptor, line cord, battery pack (1), printed quick user's guide and user's manual (CD).

Model/Order No.	Description
MT9083A2/B2/C2	ACCESS Master base unit, Enhanced display for indoor/outdoor use
Standard Accessories	
	Power Cord
Z1625A	Replacement AC Adapter for MT9083 Series
Z0921A	Replacement Battery Pack for MT9083 Series
W3644AE	CD of MT9083 Series Operation Manual

2) Select Optical Configuration

Includes choice of OTDR connector adapters – select in step 5 below.

MT9083C2 Series (OTDR Ultra-high Performance Model)

Model/Order No.	Wavelength	Application
MT9083C2-053	1310/1550 nm, SM	General-purpose model for construction, maintenance and fault location
MT9083C2-057	1310/1550/1625 nm, SM	General-purpose plus enhanced macrobend detection at 1625 nm

MT9083B2 Series (OTDR High Performance Model)

Model/Order No.	Wavelength	Application
MT9083B2-053	1310/1550 nm, SM	General-purpose model for construction, maintenance and fault location
MT9083B2-055	1310/1550 nm & 1650 nm, SM	General-purpose models for construction, maintenance and fault location plus In-service measurement – integrated filter to block transmissions
MT9083B2-056	1310/1490/1550 nm, SM	General-purpose plus 1490 nm for FTTx/PON applications
MT9083B2-057	1310/1550/1625 nm, SM	General-purpose plus enhanced macrobend detection at 1625 nm
MT9083B2-058	1310/1490/1550/1625 nm, SM	Full spectrum characterization for CWDM applications
MT9083B2-063	850/1300 nm MM, 1310/1550 nm SM	Best unit for contractors or anyone who installs or maintains hybrid networks

MT9083A2 Series (OTDR Base Model)


Model/Order No.	Wavelength	Application
MT9083A2-073	1310/1550 nm, SM	General-purpose model for construction, maintenance and fault location
MT9083A2-055	1310/1550 nm & 1650 nm, SM	
MT9083A2-057	1310/1550/1625 nm, SM	General-purpose plus enhanced macrobend detection at 1625 nm
MT9083A2-063	850/1300 nm MM, 1310/1550 nm SM	Best unit for contractors or anyone who installs or maintains hybrid networks

Note: Models noted feature user-selectable enhanced range (ER) for measuring PON systems/detecting faults in short time and high resolution (HR) for the shortest dead zone.

3) Select Factory Installed Options

Must be added as separate, chargeable line items.

Model/Order No.	Description
MT9083A2/B2/C2-010	Protector option (includes rubber bumpers, display cover and shoulder strap)



Without Protector option-010



With Protector option-010

4) Select Loss Test Set Options



Optical Power Meter Must be added as separate, chargeable line items.	
Model/Order No.	Description
MT9083A2/B2/C2-004	SMF Optical Power Meter (UPC only)
MT9083A2/B2/C2-005	SMF High Power Optical Power Meter (UPC/APC)
MT9083A2/B2/C2-007	SMF/MMF Optical Power Meter (UPC/APC)
Visible Light Source	
Model/Order No.	Description
MT9083A2/B2/C2-002	Visible Laser Diode

5) Select Connector Types

The ACCESS Master MT9083 can be optioned to feature up to three optical ports – single mode OTDR, multimode OTDR and an Optical Power Meter (options -004, -005, and -007). Selecting a single connector code below will populate all optical ports with that connector type or customer can select different adapters by specifying the adapter for each of the three optical ports – see examples below.

Optical Connectors One adapter type is provided for each port at no charge - must be added as separate line items. NOTE: FC-APC and SC-APC are not available for MM OTDR or Optical Power Meter.			
Model/Order No.	Description	Model/Order No.	Description
MT9083A2/B2/C2-025	FC-APC Connector - single mode OTDR only (additional charge applies)	MT9083A2/B2/C2-038	ST Connector
MT9083A2/B2/C2-026	SC-APC Connector - single mode OTDR only (additional charge applies)	MT9083A2/B2/C2-039	DIN Connector
MT9083A2/B2/C2-037	FC Connector	MT9083A2/B2/C2-040	SC Connector

Note: UPC and APC connectors are not compatible – the internal optics are different and must be specified at time of order.



Examples:

	Specify UPC Connector		Specify APC Connector	
Configuration	MT9083B2-053 with MT9083B2-004 Customer can specify "SC/UPC type for the SM OTDR" port and "FC/UPC type for the OPM" port.	MT9083A2-063 with no options Customer can specify "FC/UPC type for the SM OTDR" port and "FC/UPC type for the OTDR MM" port.	MT9083C2-053 with MT9083C2-007 Customer can specify "SC/APC type for the SM OTDR" port and "SC/UPC type for the OPM" port.	MT9083B2-063 with no options Customer can specify "FC/APC type for the SM" port and "FC/UPC type for the MM" port.
Order No.	MT9083B2 MT9083B2-053 MT9083B2-037 MT9083B2-040	MT9083A2 MT9083A2-063 MT9083A2-037*1	MT9083C2 MT9083C2-053 MT9083C2-026*2	MT9083B2 MT9083B2-063 MT9083B2-025*3

*1: Applied to both the OTDR SM port and the OPM port.

*2: The APC connector is not applied to the OPM port. The UPC connector is applied to the OPM port, automatically.

*3: The APC connector is not applied to the MM port. The UPC connector is applied to the MM port, automatically.

6) Select Accessories & Replacement Items

Accessories Must be added as separate, chargeable line items.			
Model/Order No.	Description	Model/Order No.	Description
W3644AE	MT9083 Series ACCESS Master Operation Manual (CD)	J1027	P4 Power Cord
W3634AE	MT9083 Operation Manual (Hard copy)	J1511	C7 Power Cord (for Korea)
W3637AE	MT9083 Quick User's Guide (Hard copy)	J1745	S3 Power Cord (for Oceania)
B0582A	Soft Carrying Case	Z1632A	Battery Charger
B0690A	Soft Bag	J1530A	SC Plug-in Converter (UPC(P)-APC(J))
B0583A	Hard Transit Case (for MT9083 - attache style)	J1531A	SC Plug-in Converter (APC(P)-UPC(J))
B0549	Hard Carry Case (for MT9083 with handle and wheels)	J1532A	FC Plug-in Converter (UPC(P)-APC(J))
Z0921A	Battery Pack (for MT9083)	J1533A	FC Plug-in Converter (APC(P)-UPC(J))
Z1625A	AC Adapter	J1534A	LC-SC Plug-in Converter (for SM, SC(P)-LC(J))
J0979	A-2 (Japan) Power Cord	J1535A	LC-SC Plug-in Converter (for MM, SC(P)-LC(J))
J0980	A-2 Power Cord (for USA, Canada, Taiwan)	J1295	Car Plug Cord
J0981	B4 Power Cord	J1480A	USB-Ethernet Converter
J0982	C7 Power Cord (for EU)	G0306B	Connector Video Inspection Probe Lite Option (× 400)
J0983	S3 Power Cord	NETWORKS	PC Emulation Software for Data Analysis and Reporting

Retrofit Options for existing units – unit must be returned to authorized service center	
MT9083A2/B2/C2-110	Protector Option (Retrofit)
MT9083A2/B2/C2-107	SMF/MMF Optical Power Meter (Retrofit)
MT9083A2/B2/C2-104	SMF Optical Power Meter (Retrofit)
MT9083A2/B2/C2-105	SMF High Power Optical Power Meter (Retrofit)

Replacement Adapters			
Type	OTDR and Power Meters (MT9083A2/B2/C2-004)	Power Meter (MT9083A2/B2/C2-005 only)	Power Meter (MT9083A2/B2/C2-007 only)
FC	J0617B, J1603A (Phosphor bronze)	MA9005B	LP-FC
Angled FC (AFC)	J0739A*	MA9005B	LP-FC
ST	J0618D	MA9005B-38	LP-ST
DIN	J0618E	MA9005B-39	LP-DIN
HMS-10A	J0618F	MA9005B-43	N/A
SC (UPC or APC)	J0619B, J1602A (Phosphor bronze)	MA9005B-40	LP-SC

*: OTDR port only



Soft Carrying Case (B0582A)



B0690A Softbag



Hard Carrying Case (B0583A)-Attache style



Hard Carrying Case (B0549)



J1530A to J1535A
Plug-in Converter
(The photo shows the J1534A)



Video Inspection Probe (× 400)
(G0306B)

MT9090 Series Network Master

MU909014x/15x μ OTDR Module

Compact OTDR for full automatic verification of optical networks, FTTH-PON, Metro and Core.

MU909060A GigE Module

Dedicated field test solution for installation and troubleshooting Ethernet links in the access network.

MU909020A OCA Module

Compact CWDM channel analyzer to verify power levels, drift and channel presence of CWDM networks.



MU909014x/15x

MT1000A Network Master Pro Network Master Pro

MU100010A 10G Multirate Module

MU100011A 100G Multirate Module

Installing the MU100010A or MU100011A in the MT1000A supports commissioning and maintenance tests of communications networks operating at speeds from 1.5 Mbps to 100 Gbps. In addition to Ethernet, OTN, etc., networks, the CPRI, OBSAI, and SyncE protocols used by mobile-network base stations are supported too.

MU100020A OTDR Module 1310/1550 nm SMF

MU100021A OTDR Module 1310/1550/850/1300 nm SMF/MMF

MU100022A OTDR Module 1310/1550/1625 nm SMF

Installing an OTDR Module MU100020A/MU100021A/MU100022A provides the OTDR functions required for optical fiber I&M. Work efficiency is increased by all-in-one support for optical fiber tests and data communications network commissioning.

I&M tests of communications networks can be executed by simultaneously installing the MU10001xA. In addition to supporting Ethernet, OTN, etc., networks, Mobile base station CPRI and OBSAI, as well as SyncE protocols are also supported.



Anritsu

Specifications are subject to change without notice.

● United States

Anritsu Company

1155 East Collins Blvd., Suite 100, Richardson,
TX 75081, U.S.A.
Toll Free: 1-800-267-4878
Phone: +1-972-644-1777
Fax: +1-972-671-1877

● Canada

Anritsu Electronics Ltd.

700 Silver Seven Road, Suite 120, Kanata,
Ontario K2V 1C3, Canada
Phone: +1-613-591-2003
Fax: +1-613-591-1006

● Brazil

Anritsu Eletronica Ltda.

Praça Amadeu Amaral, 27 - 1 Andar
01327-010 - Bela Vista - Sao Paulo - SP
Brazil
Phone: +55-11-3283-2511
Fax: +55-11-3288-6940

● Mexico

Anritsu Company, S.A. de C.V.

Av. Ejército Nacional No. 579 Piso 9, Col. Granada
11520 México, D.F., México
Phone: +52-55-1101-2370
Fax: +52-55-5254-3147

● United Kingdom

Anritsu EMEA Ltd.

200 Capability Green, Luton, Bedfordshire, LU1 3LU, U.K.
Phone: +44-1582-433200
Fax: +44-1582-731303

● France

Anritsu S.A.

12 avenue du Québec, Bâtiment Iris 1- Silic 612,
91140 VILLEBON SUR YVETTE, France
Phone: +33-1-60-92-15-50
Fax: +33-1-64-46-10-65

● Germany

Anritsu GmbH

Nemetschek Haus, Konrad-Zuse-Platz 1
81829 München, Germany
Phone: +49-89-442308-0
Fax: +49-89-442308-55

● Italy

Anritsu S.r.l.

Via Elio Vittorini 129, 00144 Roma, Italy
Phone: +39-6-509-9711
Fax: +39-6-502-2425

● Sweden

Anritsu AB

Kistagången 20B, 164 40 KISTA, Sweden
Phone: +46-8-534-707-00
Fax: +46-8-534-707-30

● Finland

Anritsu AB

Teknobulevardi 3-5, FI-01530 VANTAA, Finland
Phone: +358-20-741-8100
Fax: +358-20-741-8111

● Denmark

Anritsu A/S

Torveporten 2, 2500 Valby, Denmark
Phone: +45-7211-2200
Fax: +45-7211-2210

● Russia

Anritsu EMEA Ltd.

Representation Office in Russia
Tverskaya str. 16/2, bld. 1, 7th floor.
Moscow, 125009, Russia
Phone: +7-495-363-1694
Fax: +7-495-935-8962

● Spain

Anritsu EMEA Ltd.

Representation Office in Spain
Edificio Cuzco IV, Po. de la Castellana, 141, Pta. 5
28046, Madrid, Spain
Phone: +34-915-726-761
Fax: +34-915-726-621

● United Arab Emirates

Anritsu EMEA Ltd.

Dubai Liaison Office

902, Aurora Tower,
P O Box: 500311- Dubai Internet City
Dubai, United Arab Emirates
Phone: +971-4-3758479
Fax: +971-4-4249036

● India

Anritsu India Private Limited

2nd & 3rd Floor, #837/1, Binnamangla 1st Stage,
Indiranagar, 100ft Road, Bangalore - 560038, India
Phone: +91-80-4058-1300
Fax: +91-80-4058-1301

● Singapore

Anritsu Pte. Ltd.

11 Chang Charn Road, #04-01, Shriro House
Singapore 159640
Phone: +65-6282-2400
Fax: +65-6282-2533

● P.R. China (Shanghai)

Anritsu (China) Co., Ltd.

Room 2701-2705, Tower A,
New Caohejing International Business Center
No. 391 Gui Ping Road Shanghai, 200233, P.R. China
Phone: +86-21-6237-0898
Fax: +86-21-6237-0899

● P.R. China (Hong Kong)

Anritsu Company Ltd.

Unit 1006-7, 10/F., Greenfield Tower, Concordia Plaza,
No. 1 Science Museum Road, Tsim Sha Tsui East,
Kowloon, Hong Kong, P.R. China
Phone: +852-2301-4980
Fax: +852-2301-3545

● Japan

Anritsu Corporation

8-5, Tamura-cho, Atsugi-shi, Kanagawa, 243-0016 Japan
Phone: +81-46-296-6509
Fax: +81-46-225-8352

● Korea

Anritsu Corporation, Ltd.

5FL, 235 Pangyoeyeok-ro, Bundang-gu, Seongnam-si,
Gyeonggi-do, 13494 Korea
Phone: +82-31-696-7750
Fax: +82-31-696-7751

● Australia

Anritsu Pty. Ltd.

Unit 20, 21-35 Ricketts Road,
Mount Waverley, Victoria 3149, Australia
Phone: +61-3-9558-8177
Fax: +61-3-9558-8255

● Taiwan

Anritsu Company Inc.

7F, No. 316, Sec. 1, NeiHu Rd., Taipei 114, Taiwan
Phone: +886-2-8751-1816
Fax: +886-2-8751-1817