

MODEL **226****LASER/LED**  
LASERMOUNT

The 226 Laser/LED LaserMount is a full-featured laser fixture with integrated temperature control and easy device connections.



### ACTIVE HEATING AND COOLING

The 226 LaserMount includes a built-in Peltier device and temperature sensor for bi-polar temperature control.



### CUSTOMIZABLE COPPER COLD PLATE

100% copper cold-plate with breadboard and STAR LED mounting holes. Hard nickel plating for maximum performance and scratch resistance. Custom mounting configuration available.



### MINIMAL LIGHT ABSORPTION

The clear anodized aluminum material absorbs a minimum of light when used within an integrating sphere.



### STANDARDIZED CABLE CONNECTORS

Connect to Arroyo Instruments laser drivers and temperature controllers with standard DB-9 and DB-15 cables.



### QUICK DISCONNECTS

Two 2mm banana jacks in the side of the mount allow quick electrical connections. One set of leads is included with the mount.

## AT-A-GLANCE

Supported Laser Packages

- ▶ STAR LED
- ▶ General purpose

Cooling Mode


- ▶ Active Heating & Cooling

Thermal Capacity

- ▶ 2.4 Watts

2 mm Banana Jacks

- ▶ Quick, easy connections



## THERMISTOR TEMPERATURE SENSOR

The model 226 LaserMount offers the option of a 10K thermistor for highly sensitive temperature feedback from 0°C to 70°C.

**Highly sensitive temperature sensor,  
built in.**