

2G/3G Real-time Temp & RH Monitor ——TT11-3G

24/7 GPS Location & Temp & RH Management

- Access Information w/o Opening the Door
- High Precise Temp & RH Sensor
- Low Battery Level Notification



Features:

- * Real-time GPS location, temperature and humidity management
- * Three buttons for quick operation
- * High precise and built-in temperature and humidity sensor
- * Easily USB and SMS configuration
- * Temperature and humidity alarm notification
- * Low battery level notification
- * LED lights indicating for different status
- * Access information without opening the door



Specifications:

Dimension	122mm*81mm*30.8mm
N.W	250g
Inner Lithium Battery	Built-in 3.7V/4500mAh lithium battery (rechargeable)
Operating Temperature Range	-20°C ~ +60°C
Operating Humidity Range	Up to 85%RH (non-condensing)
Temperature Detection Accuracy	±0.3°C
Humidity Detection Accuracy	±3%RH
2G Frequency	GSM 850/900/1800/1900MHz
3G Frequency	WCDMA 800/850/900/1900/2100MHz
Flash Memory	Can store 8000pcs data
Power Consumption	Active mode (avg.) < 180mA
	Sleep mode (2G/3G module off) (avg.) < 0.1mA
	Sleep mode (2G/3G module on) (avg.) < 3.5mA
Transmit Interval	1min - 60mins (user definable)
Low Power Alarm	Yes (user definable)
Temperature & Humidity Alarm	Yes (user definable)
Button Function	Turn on / Turn off / Query device status
LED Indicator	Status / Power



Cloud Web Platform
(Email/SMS Alarm)