



WM-966



Workpiece Mounting Unit - Model 966

The ADT Workpiece Mounting Unit-Model 966 enables mounting of wafers/substrates to frames, using various kinds of tape. The system is offered in 6"/8" and 8"/12" configurations.

With smart, state-of-the-art features such as: a built-in, automatic reeling and removal of UV tape protective backing, ESD (Electrostatic Discharge) protection and many other advanced customization and control options, the system exhibits the highest level of design and performance available.

System Highlights:

- Uniform mounting and tensioning without forming air bubbles
- Built-in reeling and removal of UV tape backing
- Compatibility with all film frames
- Programmable temperature regulation
- Built-in circular blade cuts leftover tape
- Optional ESD protection
- Optional non-contact mounting

Uniform Mounting And Tensioning



12" Model

8" Model

WM-966



Standard Features

- Handles as standard 6" and 8" workpiece frames, or 8" and 12" workpiece frames (per customer specifications)
- Compatible with regular tape or UV tape
- Built-in controller regulates the temperature (up to 70° C) for consistent performance
- Automatic reeling and removal of UV tape protective backing
- Alignment pins enable precise orientation of frames
- Magnets hold and secure the frame during mounting
- Vacuum pressure holds the workpiece steady
- Engraved markings on the chuck aid in centering and aligning workpieces
- Circular blade cuts the leftover tape from the workpiece after mounting

WM-966 Special (Optional) Features

- ESD (Electrostatic Discharge) protection eliminates static electricity build-up
- 4" & 5" frame handling
- Chuck customization for multi-panel applications
- Non-contact mounting
- Plastic frame handling

Specifications

	Model 966-6", 8"	Model 966-8", 12"
Dimensions	12" H x 15.5" W x 31.5" D	13" H x 22" W x 39.5" D
Weight	99.2 lbs (45 kg)	132.3 lbs (60 kg)
Line voltage	100-120 V AC, 60 Hz, single phase or 220-240 V AC, 50 Hz single phase	
Air pressure	80 PSI	80 PSI
Air consumption	120 L/min	120 L/min



Circular blade cuts leftover tape



Automatic reeling and removal of UV tape backing



Programmable temperature regulation

Uniform Mounting And Tensioning



Headquarters
 Advanced Dicing Technologies Ltd.
 Advanced Technology Center, Haifa 31905
 Israel
 Tel: 972-4-8545222
 Fax: 972-4-8550001
 Email: sales@adt-co.com
 www.adt-dicing.com

USA Subsidiary
 Advanced Dicing Technologies Inc.
 1155 Business Center Drive, Horsham, PA 19044
 USA
 Toll free: 800-604-4950
 Tel: 215-773-9155
 Fax: 215-773-9844
 Email: us-support@adt-co.com



China RO
 1st. floor, Building 19, No. 600 Minsheng
 Road, PuDong
 Shanghai 201203,
 China
 Tel: 8621-5093-9293
 Fax: 8621-6879-0868
 Email: china_support@adt-co.com