

Specifications

	HX-75	HX-100	HX-150	
Temperature Range	+5°C to +35°C			
Temperature Stability	±0.1°C			
Unit Dimensions¹ (H x W x D) <i>Inches</i> <i>Centimeters</i>	35 ¾ x 23 ¼ x 18 ¾ 90.8 x 59.0 x 47.6	39 5/8 x 26 ¼ x 21 1/8 100.6 x 66.6 x 53.6		
Reservoir Volume <i>Gallons</i> <i>Liters</i>	5.0 19.0	8.0 30.3		
Shipping Weight <i>Pounds</i> <i>Kilograms</i>	261 118	300 136	320 145	
	HX-200	HX-300	HX-500	HX-750
Temperature Range	+5°C to +35°C			
Temperature Stability	±0.1°C			
Unit Dimensions^{1,2} (H x W x D) <i>Inches</i> <i>Centimeters</i>	45 7/8 x 33 ¾ x 25 ¼ 116.5 x 85.7 x 64.1		50 5/8 x 46 x 28 ¾ 128.3 x 116.8 x 73.0	63 ¾ x 46 x 29 162.0 x 116.8 x 73.6
Reservoir Volume <i>Gallons</i> <i>Liters</i>	15.0 56.8		28.0 106.0	40.0 151.0
Shipping Weight <i>Pounds</i> <i>Kilograms</i>	471 214	531 241	746 338	971 440

1. For additional dimensions see page 47.

2. HX-750 with a water-cooled refrigeration system has the same dimensions as the HX-500.